

Green Energy Test Report



区分	C重油 100%	C重油 + 水 70% 30%	C重油 + 廃食用油 + 水 30% 40% 30%	C重油 + 海水 70% 30%
発熱量(Kcal/L)	10,520	9,900	7,090	9,610
比重(15/4度)	0.9497	0.9663	0.9606	0.9483
残留炭素 (%)	6.63%	4.36%	3.50	6.09%
灰分 (%)	0.01%	0.12%	0.07%	0.12%
硫黄分 (%)	1.50%	0.80%	0.60%	1.40%
Pb(ppm)	9	2	6	8
Cd(ppm)	ND	ND	ND	ND
硫酸化物 (ppm)	Avg.790	Avg.640	Avg.330	Avg.600
粉塵 (mg/S ^m)	Avg.290	Avg.140	AVG50	Avg.410
窒素化合物(ppm)	250-300	180-210	10-170	180-200
一酸化炭素(ppm)	30-35	15-20	10-15	10-15
煤煙(度)	2度以下	1度以下	1度以下	1度以下
塩化水素 (ppm)	ND	ND	ND	AVG65
塩素 (ppm)	ND	ND	ND	ND
フッ素化合物(ppm)	ND	ND	ND	ND
アンモニア (ppm)	ND	ND	ND	ND
硫化水素 (ppm)	ND	ND	ND	ND
酸素 (ppm)	2.5~3.0%	6.5~7.0%	8.5~9.0%	8.5~9.0%